



**Mechanical characteristics**

cables  
 interface dimensions acc. to assembly code  
     centre conductor  
     outer conductor  
 mating life  
 coupling torque

**Components**

centre contact  
 outer contact  
 other metal parts  
 insulator  
 gasket

**Electrical characteristics**

impedance  
 frequency  
 return loss  
 insertion loss  
 working voltage  
 voltage proof  
 insulation resistance  
 contact resistance  
     centre contact  
     outer contact

**Environmental**

operating temp.  
 protection class  
 RoHS compliant

**Mechanische Eigenschaften**

Kabel  
 Steckgesicht nach Montageanleitung  
     Innenleiter  
     Außenleiter  
 Steckzyklen  
 Kupplungsdrehmoment

**Bauteile**

Innenkontakt  
 Außenkontakt  
 sonstige Metallteile  
 Isolierung  
 Dichtung

**Elektrische Eigenschaften**

Wellenwiderstand  
 Frequenz  
 Rückflussdämpfung  
 Einfügedämpfung  
 Betriebsspannung  
 Prüfspannung  
 Isolationswiderstand  
 Durchgangswiderstand  
     Innenkontakt  
     Außenkontakt

**Umgebung**

Betriebstemperatur  
 Schutzklasse  
 RoHS konform

G37: 7810A Belden, LMR400 TMS, 2.7/7.7 AF Draka..  
 G42: 213RT5 Eupen, H1000 Pope,...  
 RG-213/U, RG-214/U, RG-393/U, Aircom Plus

IEC 60169-4  
 B88  
 solder / löt  
 clamp / klemm  
 >500  
 25-35 Nm

**Materials / Material**

CuBe2  
 CuZn39Pb3  
 CuZn39Pb3  
 PFA  
 NBR

**Finish / Oberfläche**

Cu2Ag5  
 CuSnZn3  
 Cu2Ni5

50 Ω  
 0-6 GHz  
 typ.: 1 GHz-35; 2 GHz-32 dB; 4 GHz-30 dB  
 < 0,1 dB  
 ≤ 1,0 kV<sub>eff</sub> / 50 Hz  
 1,5 kV<sub>eff</sub> / 50 Hz  
 ≥ 10 GΩ  
 ≤ 0,4 mΩ  
 ≤ 0,2 mΩ

-40°C / +85°C  
 IP 67 (IEC 60529)  
 2002/95/EC

				2008	Datum/ date	Name/ name	Gewicht/ weight [g]	Oberfläche/ surface [mm <sup>2</sup> ]	Werkstoff/ material
				gez./ drawn	12.06.	GF			
				gepr./ appr.	18.06.08	PU			Oberfläche/ finish
				Norm/ stand.					
Maßstab/ scale	Benennung/ title			<div style="text-align: center;"> <p><b>7-16 Straight Jack</b> <b>7-16 Kabelbuchse</b></p> </div>					
2:1									
untol. Maße/ dim. without tolerances according to	Untert./doc. type	Zeichnungsnr./ drawing no.		<div style="text-align: center;"> <p>Maße/ dimensions: mm</p> </div>					
	K	J01121A0177							
Änd./ rev. index	Änderungsmittelung/ revision code	Datum/ date	Name/ name	Ersatz für/ replaces		Original : DIN A4			
						Blatt/ sheet 1 von/ of 1			